

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

ENTITY (As Used on Label and List)
 The Ultimate ChillTic...

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name G. F. Lasswell Company	Emergency Telephone Number (713) 644-4313
Address (Number, Street, City, State and Zip Code) 7126 Kirbyville, Houston, Texas 77033	Telephone Number for Information (713) 644-4313
	Date Prepared January 2, 1996
	Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
NON-HAZARDOUS. Acrylic polymers in primary forms. Crosslinked modified acrylic polymer. Chemically neutral material.				

Section III - Physical/Chemical Characteristics

Boiling Point	n/a	Specific Gravity (H ₂ O = 1)	n/a
Vapor Pressure (mm Hg.)	n/a	Melting Point	n/a
Vapor Density (AIR = 1)	n/a	Evaporation Rate (Butyl Acetate = 1)	n/a

Solubility in Water
 Swell (does not dissolve). pH of aqueous system approx. 6.4 - 7.0

Appearance and Odor
 Colorless material with typical odor.

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) n/a	Flammable Limits n/a	LEL	UEL
----------------------------------	-------------------------	-----	-----

Extinguishing Media
 Water, CO₂, dry chemical foam

Special Fire Fighting Procedures
 Treat as Class A

Special Fire and Explosion Hazards

Dust may be explosive if mixed with air in critical proportions and in the presence of a source of ignition.

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid	None Known
	Stable	X		

Incompatibility (Materials to Avoid)
 Strong oxidizing agents

Hazardous Decomposition or Byproducts
 Thermal decomposition or combustion may product carbon monoxide and/or oxide of nitrogen.

Hazardous Polymerizations	May Occur		Conditions to Avoid	None Known
	Will Not Occur	X		

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
n/a			

Health Hazards (Acute and Chronic)
 n/a

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
n/a			

Signs and Symptom of Exposures
 Internal consumption of approximately 1.0 quart will produce nausea. Inhalation of large amount of dust will cause temporary breathing problem.

Medical Conditions
 Generally Aggravated by Exposure

n/a

Emergency and First Aid Procedures
 If large quantity ingested, drink lots of water and induce vomiting. If large quantity of dust inhaled, remove individual from dusty area.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled
 Sweep with broom or remove by vacuuming.

Waste Disposal Method
 Employ normal waste disposal method. Do not dispose in drains.

Precautions to Be Taken in Handling and Storing
 Keep in dry place.

Other Precautions
 Spilled material is slippery when wet.

Section VIII - Control Measures

Respiratory Protection (Specify Type)
 If very dusty atmosphere, wear simple gauze mask.

Ventilation	Local Exhaust	Normal Ventilation.	Special
	Mechanical (General)	None	Other
Protective Gloves	None required.		Eye Protection
			None required.

Other Protective Clothing or Equipment

None Required.

Work/Hygienic Practices Maintain good housekeeping to control dust accumulations.